# Safety Data Sheet

Issue Date: 09-Jul-2015	Revision Date: 21-Jun-2016	Version 1
	1. IDENTIFICATION	
Product Identifier Product Name	Rim Sealant Flammable, Rim Sealant - Extra Th	nick Flammable, Bead Sealer
Other means of identification SDS #	ELG-010	
Product Code	Catalog numbers: 1-799, 1-770, 1-798, 1-771, 4-799, 4-770, 4-798, 4-771, 4-772, 1-797, 1-777 2-778, 2-779, 4-797, 4-777, 4-740, 4-778, 4-779 RS-32	7, 1-740, 1-778, 1-779, 2-797, 2-777, 2-740,
UN/ID No	UN1133	
Recommended use of the chemic Recommended Use	al and restrictions on use Rubber adhesive.	
Details of the supplier of the safe Supplier Address ELGI Rubber Company, LLC 600 N. Magnolia Ave. Luling, TX 78648 Ph: 830-875-5539 Emergency Telephone Number Emergency Telephone (24 hr)	INFOTRAC 1-352-323-3500 (International) 1-800-535-5053 (North America)	
	2. HAZARDS IDENTIFICATION	
Appearance Black high viscosity	liquid Physical state Liquid	Odor Petrolic
Skin corrosion/irritation Specific target organ toxicity (single Aspiration toxicity Flammable Liquids Hazards Not Otherwise Classified		Category 2 Category 3 Category 1 Category 2
May be harmful in contact with skin	<u>.</u>	

### <u>Signal Word</u> Danger

### Hazard statements

Causes skin irritation May cause drowsiness or dizziness May be fatal if swallowed and enters airways Highly flammable liquid and vapor



### Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces. — No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof equipment Use only non-sparking tools Take precautionary measures against static discharge Keep cool

### Precautionary Statements - Response

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower If skin irritation occurs: Get medical advice/attention Wash contaminated clothing before reuse IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a poison center or doctor/physician if you feel unwell IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do not induce vomiting IN CASE OF FIRE: Use CO2, dry chemical, or foam for extinction

### **Precautionary Statements - Storage**

Store locked up Store in a well-ventilated place. Keep container tightly closed

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Other hazards

Very toxic to aquatic life with long lasting effects

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%
N-Heptane	142-82-5	80-90
Carbon Black	1333-86-4	0-5

\*\*If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.\*\*

### 4. FIRST AID MEASURES

### First Aid Measures

General Advice	Provide this SDS to medical personnel for treatment.
Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin Contact	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
Ingestion	Do not induce vomiting. Immediately call a poison center or doctor/physician. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.
Most important symptoms and eff	ects
Symptoms	Causes skin irritation. May be harmful in contact with skin. May cause drowsiness or dizziness. May cause pulmonary edema. Possible symptoms are irritation of the mucous membranes, dry cough and respiratory difficulty. Other symptoms may include dizziness, headache, nausea, and loss of coordination.
Indication of any immediate medio	cal attention and special treatment needed

Notes to PhysicianTreat symptomatically. Aspiration of material into the lungs due to vomiting can cause<br/>chemical pneumonitis which can be fatal. Epinephrine and other sympathomimetic drugs<br/>may initiate cardiac arrhythmias in persons exposed to high concentrations of hydrocarbon<br/>solvents. The use of other drugs with less arrhythmogenic potential should be considered.<br/>If sympathomimetic drugs are administered, observe for the development of cardiac<br/>arrhythmias.

### **5. FIRE-FIGHTING MEASURES**

#### Suitable Extinguishing Media

Water spray (fog). Alcohol resistant foam. Dry chemical. Carbon dioxide (CO2).

Unsuitable Extinguishing Media Do not use solid water streams.

#### Specific Hazards Arising from the Chemical

Highly flammable liquid and vapor. The liquid vapor may settle into low areas or may travel along the ground or surface to ignition sources where they might ignite or explode. Flash back possible over considerable distance.

Hazardous Combustion Products Carbon monoxide. Carbon dioxide (CO2).

### Explosion Data

Sensitivity to Static Discharge Take precautionary measures against static discharge.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool. Fight fire remotely due to the risk of explosion.

### 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

Personal Precautions	Wear protective clothing as described in Section 8 of this safety data sheet. Evacuate personnel to safe areas. Remove all sources of ignition. Ensure adequate ventilation. Avoid breathing vapors or mists.
Environmental precautions	
Environmental precautions	Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.
Methods and material for containm	nent and cleaning up
Methods for Containment	Prevent further leakage or spillage if safe to do so. Soak up and contain spill with an inert (i.e. vermiculite, dry sand or earth) absorbent material.
Methods for Clean-Up	Use only non-sparking tools. Place in properly labeled, sealed, non-leaking containers. Dispose of contents/container via a licensed waste disposal contractor. For waste disposal, see section 13 of the SDS.
	7. HANDLING AND STORAGE
Precautions for safe handling	
Advice on Safe Handling	Wash face, hands, and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing and eye/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away

dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Ground/bond container and receiving equipment. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Keep cool.

### Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a cool, well-ventilated place. Store locked up. Heat sensitive-store under inert gas.
Incompatible Materials	Strong oxidizing agents.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
N-Heptane	STEL: 500 ppm	TWA: 500 ppm	IDLH: 750 ppm
142-82-5	TWA: 400 ppm	TWA: 2000 mg/m <sup>3</sup>	Ceiling: 440 ppm 15 min
		(vacated) TWA: 400 ppm	Ceiling: 1800 mg/m <sup>3</sup> 15 min
		(vacated) TWA: 1600 mg/m <sup>3</sup>	TWA: 85 ppm
		(vacated) STEL: 500 ppm	TWA: 350 mg/m <sup>3</sup>
		(vacated) STEL: 2000 mg/m <sup>3</sup>	_
Carbon Black	TWA: 3 mg/m <sup>3</sup> inhalable fraction	TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup>
1333-86-4	_	(vacated) TWA: 3.5 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup>
		. , _	TWA: 0.1 mg/m <sup>3</sup> Carbon black in
			presence of Polycyclic aromatic
			hydrocarbons PAH

Appropriate engineering controls	
Engineering Controls	Apply technical measures to comply with the occupational exposure limits. Showers Eyewash stations Ventilation systems. Explosion-proof general and local exhaust ventilation.
Individual protection measures, s	such as personal protective equipment
Eye/Face Protection	Wear goggles or chemical safety glasses. Refer to 29 CFR 1910.133 for eye and face protection regulations.
Skin and Body Protection	Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Refer to 29 CFR 1910.138 for appropriate skin and body protection.
Respiratory Protection	If necessary, wear a MSHA/NIOSH-approved respirator. Refer to 29 CFR 1910.134 for respiratory protection requirements.
General Hygiene Consideration	<b>ons</b> Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and immediately after handling the product.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state Appearance Color	Liquid Black high viscosity liquid Black	Odor Odor Threshold	Petrolic Not determined
Property pH Melting Point/Freezing Point	<u>Values</u> Not determined -90.0 to -90.1 °C / -131.7 to -130.3 °F	Remarks • Method	
Boiling Point/Boiling Range Flash Point Evaporation Rate Flammability (Solid, Gas) Flammability Limits in Air Upper Flammability Limits Lower Flammability Limit Vapor Pressure	98.1 to 98.7 °C 208.5 to 209.6 °F -4.0 °C / 24.8 °F 4 Not determined 7% 1.1% 110.7 hPa (83.0 mmHg) at 37.7 °C	(butyl acetate = 1) Not applicable	
Vapor Density	(99.9°F) , 53.3 hPa (40.0 mmHg) at 20.0 °C (68.0°F) 3.30	(Air=1)	
Relative Density Water Solubility Solubility in other solvents Partition Coefficient Auto-ignition Temperature Decomposition Temperature Kinematic Viscosity Dynamic Viscosity Explosive Properties Oxidizing Properties	0.684 g/mL at 25°C (77°F) Not determined Insoluble log Pow > 3.000 223.0 °C / 433.4 °F Not determined Not determined Not determined Not determined Not determined		

#### **Other Information**

Molecular weight VOC Content (%)

100.2 g/mol N/A

### **10. STABILITY AND REACTIVITY**

### **Reactivity**

Not reactive under normal conditions.

### **Chemical Stability**

Stable under recommended storage conditions.

#### **Possibility of Hazardous Reactions**

None under normal processing.

#### **Conditions to Avoid**

Heat, flames and sparks.

### **Incompatible Materials**

Strong oxidizing agents.

. . . .

### **Hazardous Decomposition Products**

None known based on information supplied.

### **11. TOXICOLOGICAL INFORMATION**

### Information on likely routes of exposure . .

Product Information	
Eye Contact	Avoid contact with eyes.
Skin Contact	Causes skin irritation. May be harmful in contact with skin.
Inhalation	May cause drowsiness or dizziness. May cause irritation to the mucous membranes and upper respiratory tract.
Ingestion	May be fatal if swallowed and enters airways. May cause gastrointestinal irritation, nausea, diarrhea, and vomiting.

### Component Information

Chemical Name	ATEmix (oral)	ATEmix (dermal)	Inhalation LC50
N-Heptane 142-82-5	-	= 3000 mg/kg (Rabbit)	= 103 g/m³ (Rat)4 h
Carbon Black 1333-86-4	> 15400 mg/kg (Rat)	>3 g/kg (Rabbit)	-

#### Information on physical, chemical and toxicological effects

Symptoms

Please see section 4 of this SDS for symptoms.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

### Carcinogenicity

Carbon black is a possible carcinogen when it appears as a respirable dust.

	ACGIH	IARC	NTP	OSHA
Carbon Black	A3	Group 2B		Х
1333-86-4				
A3 - Animal Carcinogen IARC (International Agency Group 2B - Possibly Carcinog	enic to Humans	ll Hygienists) f the US Department of Labor)		
STOT - single exposu	re May cause	drowsiness or dizziness.		
STOT - single exposu Aspiration hazard	.,	drowsiness or dizziness. I if swallowed and enters airv	Nays.	

## ATEmix (dermal) 3,158.00 mg/kg

ATEmix (inhalation-dust/mist) 114.00 mg/L

### 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

Very toxic to aquatic life with long lasting effects.

#### Component Information

Chemical Name	Algae/aquatic plants	Fish	Crustacea
N-Heptane		375.0: 96 h Cichlid fish mg/L LC50	10: 24 h Daphnia magna mg/L
142-82-5			EC50
Carbon Black			5600: 24 h Daphnia magna mg/L
1333-86-4			ÉC50

#### Persistence/Degradability

Not determined.

#### **Bioaccumulation**

Not determined.

#### <u>Mobility</u>

Chemical Name	Partition Coefficient	
N-Heptane	4.66	
142-82-5		

#### Other Adverse Effects

Not determined

### **13. DISPOSAL CONSIDERATIONS**

### Waste Treatment Methods

Disposal of Wastes	Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.
Contaminated Packaging	Disposal should be in accordance with applicable regional, national and local laws and regulations.

### California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status	
N-Heptane	Toxic	
142-82-5	Ignitable	

### **14. TRANSPORT INFORMATION**

### Note

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

<u>DOT</u> UN/ID No Proper Shipping Name Hazard Class Packing Group	UN1133 Adhesives 3 II
IATA UN/ID No Proper Shipping Name Hazard Class Packing Group	UN1133 Adhesives 3 II
IMDG UN/ID No Proper Shipping Name Hazard Class Packing Group	UN1133 Adhesives 3 II

Yes

**Marine Pollutant** 

Page 8/10

### **15. REGULATORY INFORMATION**

### International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/E LINCS	ENCS	IECSC	KECL	PICCS	AICS
N-Heptane	Х	Х	Х	Present	Х	Present	Х	Х
Carbon Black	Х	Х	Х	Present	Х	Present	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

### US Federal Regulations

### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

#### CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

### US State Regulations

### California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65	
Carbon Black - 1333-86-4	Carcinogen	

### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
N-Heptane 142-82-5	Х	X	X
Carbon Black 1333-86-4	Х	X	X

### **16. OTHER INFORMATION**

NFPA HMIS	Health Hazards 1 Health Hazards 1	Flammability 3 Flammability 3	Instability 0 Physical hazards 0	Special Hazards Not determined Personal Protection Not determined
lssue Date: Revision Date: Revision Note:	09-Jul-2015 21-Jun-2016 New format			

**Disclaimer** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet