Product Identifier: Rubber Buffer Stock Number: A586 Date of the latest revision of the safety data sheet: 04-12-2017 Supercedes:

1 Identification	
(a) Product Identifier:	Rubber Buffer
Stock Number:	A586
(b) Other means of identification:	
Synonyms:	None Known
(c) Recommended use and restrictions on	use:
Recommended use:	Buffing Solution
Restrictions on use:	Uses not described above.
(d) Initial Supplier Identifier:	Stoner Incorporated
Manufacture/Distributor:	1070 Robert Fulton Hwy.
	Quarryville, PA 17566
Tel No.:	1-800-227-5538
Email address:	customerservice@stonersolutions.com
(e) Emergency telephone number and any restrictions on the use of that number, if applicable:	1-800-424-9300 [CHEMTREC]

2 Hazard identification

(a) Classification of the hazardous product, namely the appropriate category or subcategory of the hazard class identified in Subparts 2 to 19 of Part 7 or Subparts 1 to 11 of Part 8, or a name that is its substantive equivalent, or for Subpart 20 of Part 7 and Subpart 12 of Part 8, the category of the hazard class or a description of the identified hazard: Flammable Liquid Category 1 Aspiration Hazard Category 1 Skin Corrosion/Irritation Category 2 Carcinogenicity Category 2 Reproductive Toxicity Category 2 Specific Target Organ SystemicToxicity (STOT) - Single Exposure Category 3 Acute Toxicity - Inhalation Vapour Category 4

(b) Information elements referred to in section 3 of Annex 3 of the GHS and in paragraphs 3(1)(d) to (f) of these Regulations for each of those categories or subcategories. If the required information element is a symbol, either the name of the symbol or the symbol itself may be used:

GHS Hazard class symbols:



Signal word: Hazard statements:

Danger Extremely flammable liquid and vapour; May be fatal if swallowed and enters airways; Harmful in contact with skin or if inhaled; Causes skin

Product Identifier: Rubber Buffer Stock Number: A586 Date of the latest revision of the safety data sheet: 04-12-2017 Supercedes:

	irritation; May cause drowsiness or dizziness; Suspected of causing
	cancer.; Suspected of damaging fertility or the unborn child.
Precautionary statements:	
Prevention:	Obtain special instructions before use. Do not handle until all safety
	precautions have been read and understood. Keep away from
	heat/sparks/open flames/hot surfaces. No smoking. Ground/bond
	container and receiving equipment. Use explosion-proof
	[electrical/ventilating/lighting] equipment. Use only non-sparking tools.
	Take precautionary measures against static discharge. Avoid breathing
	dust/fume/gas/mist/vapours/spray.Wash thoroughly after handling. Use
	only outdoors or in a well-ventilated area. Wear protective
	gloves/protective clothing/eye protection/face protection.
Response:	IF SWALLOWED: Immediately call a POISON CENTER/doctor. If on skin:
·	Wash with plenty of water. IF ON SKIN (or hair): Take off immediately all
	contaminated clothing. Rinse skin with water/shower.IF INHALED:
	Remove victim to fresh air and keep at rest in a position comfortable for
	breathing. IF exposed or concerned: Get medical advice/ attention. Call a
	POISON CENTER/doctor if you feel unwell. Specific treatment (see on this
	label). Do NOT induce vomiting. If skin irritation occurs: Get medical
	advice/attention. Take off contaminated clothingand wash it before
	reuse. In case of fire: Use an approprate extinguisher (see section 5) to
	extinguish.
Storage:	Store in a well-ventilated place. Keep container tightly closed. Store in a
	well-ventilated place. Keep cool. Store locked up.
Disposal:	Dispose of contents/container to a suitable disposal site in accordance
	with local/national/international regulations.
	with local hational methational regulations.

(c) Other hazards known to the supplier with respect to the hazardous product:

Physical hazards not otherwise	None Known
classified	

Health hazards not otherwise classified None Known

3 Composition/information on ingredients

Chemical Name	Common name and synonyms	CAS registry number and any unique identifiers	Concentration
Aliphatic hydrocarbons	None Known	142-82-5	60 - 80
Xylene	None Known	1330-20-7	20 - 40
Ethyl benzene	None Known	100-41-4	1-10

Product Identifier: Rubber Buffer Stock Number: A586 Date of the latest revision of the safety data sheet: 04-12-2017 Supercedes:

4 First-aid measures				
(a) A description of necessary first aid measures, subdivided according to the different routes of exposure (inhalation, ingestion, skin and eye contact): Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If				
	breathing is difficult, give oxygen. Keep the victim warm and quiet. Seek immediate medical attention.			
Eye contact:	Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.			
Skin Contact:	Wash clothing before reuse. Seek medical attention if symptoms persist. In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes.			
Ingestion:	Contact a physician, medical facility, or poison control center immediately. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Aspiration into the lungs can cause serious damage. Do not induce vomiting.			
(b) The most important symptoms and effects, whether acute or delayed:	May be fatal if swallowed and enters airways Harmful in contact with skin or if inhaled Causes skin irritation May cause drowsiness or dizziness			
(c) An indication of immediate medical attention and special treatment needed, if necessary:	Aspiration during swallowing or vomiting may severely damage the lungs. This material is an aspiration hazard. Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life support. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting.			

5 Fire-fighting measures

(a) Suitable and unsuitable extinguishing media:	
Suitable extinguishing media:	Use CO2, foam or dry chemical.
Unsuitable extinguishing media:	Not available
(b) Specific hazards arising from the	This product contains a component(s) that is considered a flammable
hazardous product, such as the nature	liquid, which has vapors that are heavier than air and may travel along
of any hazardous combustion:	the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. "Empty" containers retain product residue and can be dangerous.
(c) Special protective equipment and precautions for firefighters:	Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area.

Product Identifier: Rubber Buffer Stock Number: A586 Date of the latest revision of the safety data sheet: 04-12-2017 Supercedes:

6 Accidental release measures		
(a) Personal precautions, protective equipment and emergency procedures:	Not available	
(b) Methods and materials for	Place absorbent materials into container and close it tightly. Dispose of	
containment and cleaning up:	container properly. Clean up with absorbent material. If runoff occurs, notify authorities as required. Avoid run-off into storm sewers and ditches which may lead to natural waterways. Stop or reduce discharge if it can be done safely. Wear appropriate personal protective equipment (PPE). Remove all sources of ignition. Ventilate contaminated area.	
7 Handling and storage		
(a) Precautions for safe handling:	Do not store containers in excessive heat or direct sunlight. Avoid contact with eyes. If ventilation is not sufficient, wear proper respiratory equipment. Do not use near ignition sources. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death. Use with adequate ventilation. Avoid prolonged or repeated breathing of vapor. Avoid prolonged or repeated contact with skin. This material can be harmful or irritating. Normal precautions common to safe manufacturing practice should be followed in handling and storage.	
(b) Conditions for safe storage, including any incompatibilities:		
Conditions for safe storage:	Keep away from heat, sparks and flame. Normal precautions common to safe manufacturing practice should be followed in handling and storage. Empty container may contain residues which are hazardous. Store in a cool, dry, well ventilated area away from all sources of ignition.	
Materials to Avoid/Chemical Incompatibility:	Not available	

8 Exposure controls/personal protection

(a) Control parameters, including occupational exposure limit values or biological limit values and the source of those values:

Chemical Name	Occupational	Occupational	Occupational
	Exposure Limits -	Exposure Limits -	Exposure Limits -
	TWAs	STELs	Ceiling
Aliphatic hydrocarbons	400 PPM TWA; 1640	2050 MG/M3 STEL;	Not available

Product Identifier: Rubber Buffer Stock Number: A586 Date of the latest revision of the safety data sheet: 04-12-2017 Supercedes:

	MG/M3 TWA	500 PPM STEL	
Xylene	100 PPM TWA; 434	150 PPM STEL; 651	Not available
	MG/M3 TWA	MG/M3 STEL	
Ethyl benzene	100 PPM TWA; 434	543 MG/M3 STEL; 125	Not available
	MG/M3 TWA	PPM STEL	

Canada – British Columbia– Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Aliphatic hydrocarbons	400 PPM TWA	500 PPM STEL	Not available
Xylene	100 PPM TWA	150 PPM STEL	Not available
Ethyl benzene	100 PPM TWA	125 PPM STEL	Not available

Canada – Manitoba – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Aliphatic hydrocarbons	Not available	Not available	Not available
Xylene	Not available	Not available	Not available
Ethyl benzene	Not available	Not available	Not available

Canada – New Brunswick – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Aliphatic hydrocarbons	Not available	Not available	Not available
Xylene	Not available	Not available	Not available
Ethyl benzene	Not available	Not available	Not available

Canada – Newfoundland & Labrador – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Aliphatic hydrocarbons	Not available	Not available	Not available
Xylene	Not available	Not available	Not available
Ethyl benzene	Not available	Not available	Not available

Canada – Northwest Territories – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Aliphatic hydrocarbons	Not available	Not available	Not available
Xylene	Not available	Not available	Not available
Ethyl benzene	Not available	Not available	Not available

Product Identifier: Rubber Buffer Stock Number: A586 Date of the latest revision of the safety data sheet: 04-12-2017 Supercedes:

Canada – Nova Scotia – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Aliphatic hydrocarbons	Not available	Not available	Not available
Xylene	Not available	Not available	Not available
Ethyl benzene	Not available	Not available	Not available

Canada – Nunavut – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Aliphatic hydrocarbons	Not available	Not available	Not available
Xylene	Not available	Not available	Not available
Ethyl benzene	Not available	Not available	Not available

Canada – Ontario – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Aliphatic hydrocarbons	1635 MG/M3 TWA;	500 PPM STEL; 2045	Not available
	400 PPM TWA	MG/M3 STEL	
Xylene	Not available	Not available	Not available
Ethyl benzene	100 PPM TWA; 435	125 PPM STEL; 540	Not available
	MG/M3 TWA	MG/M3 STEL	

Canada – Prince Edward Island – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Aliphatic hydrocarbons	Not available	Not available	Not available
Xylene	Not available	Not available	Not available
Ethyl benzene	Not available	Not available	Not available

Canada – Quebec – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAEVs	Occupational Exposure Limits - STEVs	Occupational Exposure Limits - Ceiling
Aliphatic hydrocarbons	1640 MG/M3 TWA; 400 PPM TWA	2050 MG/M3 STEL; 500 PPM STEL	Not available
Xylene	100 PPM TWA; 434 MG/M3 TWA	150 PPM STEL; 651 MG/M3 STEL	Not available
Ethyl benzene	434 MG/M3 TWA; 100 PPM TWA	125 PPM STEL; 543 MG/M3 STEL	Not available

Product Identifier: Rubber Buffer Stock Number: A586 Date of the latest revision of the safety data sheet: 04-12-2017 Supercedes:

Canada – Saskatchewan – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Aliphatic hydrocarbons	Not available	Not available	Not available
Xylene	Not available	Not available	Not available
Ethyl benzene	Not available	Not available	Not available

Canada - Yukon – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Aliphatic hydrocarbons	Not available	Not available	Not available
Xylene	Not available	Not available	Not available
Ethyl benzene	Not available	Not available	Not available

Chemical Name	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL	IDLH
Aliphatic hydrocarbons	Not available	1640 MG/M3	500 PPM STEL;	Not available
		TWA; 400 PPM	2050 MG/M3	
		TWA	STEL	
Xylene	Not available	434 MG/M3	150 PPM STEL;	Not available
		TWA; 100 PPM	651 MG/M3 STEL	
		TWA		
Ethyl benzene	Not available	20 PPM TWA	Not available	Not available

(b) Appropriate engineering controls:

Local exhaust should be used in areas where exposure limits may be exceeded.

Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the SDS (from known, suspected or apparent adverse effects).

(c) Individual protection measures, such as personal protective equipment:

Respiratory Protection:	Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol. A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits.
Eye and face protection:	Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Have an eye wash station available.
Skin Protection:	The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.
Hand protection:	Not available

	$a \text{ sheat: } 0.1_{-}1_{-}2_{-}0_{-}1_{-}0_{-}0_{-}0_{-}0_{-}0_{-}0_{-}0_{-}0$	
ate of the latest revision of the safety dat upercedes:		
Other protective equipment:	Not available	
General hygiene conditions:	Wear protective gloves/protective clothing/eye protection/face	
	protection. Wash thoroughly after handling.	
9 Physical and chemical properties		
(a) Appearance, such as physical state		
and colour:		
Physical state:	Bulk liquid	
Colour:	Clear Colorless	
(b) Odour:	Mild	
	Light Hydrocarbon	
(c) Odour threshold:	Not available	
(d) pH:	Not applicable	
(e) Melting point and freezing point:	Not available	
(f) Initial boiling point and boiling	Not available	
range:		
(g) Flash point:	Not available	
(h) Evaporation rate:	Not determined	
(i) Flammability, in the case of solids	Not available	
and gases:		
(j) Upper and lower flammability or		
explosive limits:		
Upper flammable or explosive limit,	6.7	
% in air:		
Lower flammable or explosive limit,	1	
% in air:		
(k) Vapour pressure:	Not available	
(I) Vapour density:	>1	
(m) Relative density:	1	
(n) Solubility:	Not determined	
(o) Partition coefficient — n-	Not available	
octanol/water:		
(p) Auto-ignition temperature:	Not available	
(q) Decomposition temperature:	Not available	
(r) Viscosity:	Not available	

10 Stability and reactivity

(a) Reactivity:	Not available
(b) Chemical stability:	Stable.
(c) Possibility of hazardous reactions:	Not available
(d) Conditions to avoid, including static	Strong oxidizing agents.

Product Identifier: Rubber Buffer Stock Number: A586 Date of the latest revision of the safety data sheet: 04-12-2017 Supercedes:

discharge, shock or vibration:	Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces.
	Avoid contact with:
(e) Incompatible materials:	Not available
(f) Hazardous decomposition products:	Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Various hydrocarbons.

11 Toxicological information

Description of the various toxic health eff	Description of the various toxic health effects and the data used to identify those effects:		
(a) Information on the likely routes of	Skin		
exposure (inhalation, ingestion, skin and eye contact):			
(b) Symptoms related to the physical,	May be fatal if swallowed and enters airways Harmful in contact with skin		
chemical and toxicological characteristics:	or if inhaled Causes skin irritation May cause drowsiness or dizziness		
(c) Delayed and immediate effects, and chronic effects from short-term and long-term exposure: Immediate effects from short term exposure:			
Inhalation Toxicity:	High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.		
Skin Contact:	Prolonged or repeated exposure may dry the skin. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use. Symptoms may include redness, discomfort, drying and cracking, or rash.		

	Skin contact may cause irritation.
Eye Contact:	Not available
Ingestion Toxicity:	Not available

Delayed and chronic effects from long term exposure:			
Sensitization:	Not available		
Mutagenicity:	Not available		
Carcinogenicity:	Based on available information, this material cannot be classified with reguard to carcinogenicity. A component in this material has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. THIS PRODUCT CONTAINS NO COMPONENTS LISTED AS CARCINOGENIC BY IARC, NTP, OR OSHA 1910(Z)		
STOT-single exposure:	Classification has been based on toxicological information of the components in Section 3.		
STOT-repeated exposure:	Based on available data, the classification criteria are not met.		
Aspiration hazard:	Classification has been based on toxicological information of the components in Section 3.		

Product Identifier: Rubber Buffer Stock Number: A586 Date of the latest revision of the safety data sheet: 04-12-2017 Supercedes:

(d) Numerical measures of toxicity, including ATEs

Information on toxicological effects:

Acute toxicity:

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Aliphatic hydrocarbons			INHALATION LC50 Rat 103 GM/M3
Xylene	ORAL LD50 Mouse 2119 mg/kg ORAL LD50 Rat 4300 mg/kg	DERMAL LD50 Rabbit 1700 mg/kg	INHALATION LC50 Rat 5000 ppm
Ethyl benzene		DERMAL LD50 Rabbit 5000 mg/kg	INHALATION LC50 Mouse 35500 MG/M3

12 Ecological information

(a) Ecotoxicity (aquatic and terrestrial, if Not available available):

Ecological Toxicity Data:

Chemical Name	CAS registry number and any unique identifiers	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
Aliphatic hydrocarbons	142-82-5	48HR EC50 Daphnia = 1.5 mg/L 96HR EC50 Algae = 3.7 mg/L	Not available	Aquatic LC50 (24h) Fish = 4 mg/L
Xylene	1330-20-7	Aquatic LC50 (24h) Daphnia 100 - 1000 mg/L	Code:	Aquatic LC50 (96h) MINNOW 24 - 30 mg/L
Ethyl benzene	100-41-4	48HR EC50 Daphnia = 9.55 mg/L	72HR EC50 Algae 4.9 mg/L	Aquatic LC50 (96h) Rainbow Trout = 8.4 mg/L

(b) Persistence and degradability:	No data
(c) Bioaccumulative potential:	Not available
(d) Mobility in soil:	Not available
(e) Other adverse effects:	Not available

13 Disposal considerations

Information on safe handling for disposal and methods of disposal, including any contaminated packaging: Spent or discarded material is a hazardous waste.

Product Identifier: Rubber Buffer Stock Number: A586 Date of the latest revision of the safety data sheet: 04-12-2017 Supercedes:

ransportation of Dangarous Coods by lar	
ransportation of Dangerous Goods by lar	
(a) UN number: (b) United Nations proper shipping	UN1993 Flammable Liquids, n.o.s.(Contains Heptanes, Xylene)
name as provided for in the United	
Nations Model Regulations:	
(c) Transport hazard class as provided in the United Nations Model Regulations:	3
(d) Packing group as provided in the United Nations Model Regulations:	II
nternational carriage of dangerous goods	by sea (IMDG/IMO):
(a) UN number:	UN1993
(b) United Nations proper shipping name as provided for in the United	Flammable Liquids, n.o.s.(Contains Heptanes, Xylene)
Nations Model Regulations: (c) Transport hazard class as provided in the United Nations Model Regulations:	3
(d) Packing group as provided in the United Nations Model Regulations:	II
nternational carriage of dangerous goods	by air (IATA):
(a) UN number:	UN1993
(b) United Nations proper shipping name as provided for in the United Nations Model Regulations:	Flammable Liquids, n.o.s.(Contains Heptanes, Xylene)
(c) Transport hazard class as provided in the United Nations Model Regulations:	3
(d) Packing group as provided in the United Nations Model Regulations:	II
(e) Environmental hazards according to the International Maritime Dangerous Goods Code and the United Nations Model Regulations:	Not available
(f) Transport in bulk (according to Annex II of the International Convention for the Prevention of Pollution From Ships, 1973, as modified by the Protocol of 1978 (MARPOL 73/78) and the International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk (IBC Code)):	Not available
(g) Special precautions in connection	Not available

Product Identifier: Rubber Buffer Stock Number: A586 Date of the latest revision of the safety data sheet: 04-12-2017 Supercedes:

with transport or conveyance either within or outside the premises:

15 Regulatory information

Safety, health and environmental regulations, made within or outside Canada, specific to the product in question: Canada - Domestic Substances List (DSL):

Chemical Name	CAS No	Canada - Domestic Substances List (DSL)
Aliphatic hydrocarbons	142-82-5	Yes
Xylene	1330-20-7	Yes
Ethyl benzene	100-41-4	Yes

Canada - Non-Domestic Substances List (NDSL):

Chemical Name	CAS No	Canada - Non-Domestic Substances List (NDSL)
Aliphatic hydrocarbons	142-82-5	No
Xylene	1330-20-7	No
Ethyl benzene	100-41-4	No

Canada - Controlled Drugs and Substances:

Chemical Name	CAS No	CAS No Schedule I	Schedule	Schedule	Schedule	Schedule	Schedule	Schedule
Chemical Name			П	Ш	IV	v	VII	VIII
Aliphatic hydrocarbons	142-82-5	No	No	No	No	No	No	No
Xylene	1330-20-7	No	No	No	No	No	No	No
Ethyl benzene	100-41-4	No	No	No	No	No	No	No

Chemical Name	CAS No	Class A Precursors	Class B Precursors	Exempt Precursors	Class 1 Targeted Substances	Class 2 Targeted Substances
Aliphatic hydrocarbons	142-82-5	No	No	No	No	No
Xylene	1330-20-7	No	No	No	No	No
Ethyl benzene	100-41-4	No	No	No	No	No

Canada - CEPA - Schedule III Export Control List:

Chemical Name	CAS No	Part 1 Prohibited Substances	Part 2 Substances Subject to Notification or Consent	Part 3 Restricted Substances	Export Control List
Aliphatic hydrocarbons	142-82-5	No	No	No	No
Xylene	1330-20-7	No	No	No	No

Product Identifier: Rubber Buffer Stock Number: A586 Date of the latest revision of the safety data sheet: 04-12-2017 Supercedes:

Ethyl benzene100-41-4No	No	No	No
-------------------------	----	----	----

Canada CEPA - 2015 Greenhouse Gases (GHG) Subject to Mandatory Reporting:

Chemical Name	CAS No	Canada CEPA - 2015 Greenhouse Gases (GHG) Subject to Mandatory Reporting
Aliphatic hydrocarbons	142-82-5	No
Xylene	1330-20-7	No
Ethyl benzene	100-41-4	No

Canada - Narcotic Control Regulations (C.R.C., c. 1041):

Chemical Name	CAS No	Canada - Narcotic Control Regulations (C.R.C., c. 1041)
Aliphatic hydrocarbons	142-82-5	No
Xylene	1330-20-7	No
Ethyl benzene	100-41-4	No

Canada - Ontario - Toxics Reduction - List of Priority Toxics:

Chemical Name	CAS No	Canada - Ontario - Toxics Reduction - List of Priority Toxics
Aliphatic hydrocarbons	142-82-5	No
Xylene	1330-20-7	No
Ethyl benzene	100-41-4	No

Stockholm Convention on Persistent Organic Pollutants:

Chemical Name	CAS No	Stockholm Convention on Persistent Organic Pollutants
Aliphatic hydrocarbons	142-82-5	No
Xylene	1330-20-7	No
Ethyl benzene	100-41-4	No

Rotterdam Convention on the Prior Informed Consent Procedure for Certain Hazardous Chemicals and Pesticides in International Trade:

Chemical Name	CAS No	Rotterdam Convention on the Prior Informed Consent Procedure for Certain Hazardous Chemicals and Pesticides in International Trade.
Aliphatic hydrocarbons	142-82-5	No
Xylene	1330-20-7	No
Ethyl benzene	100-41-4	No

(United Nations) - Kyoto Protocol - Convention on Climate Change - Greenhouse Gases (GHGs):

Chemical Name	CAS No	(United Nations) - Kyoto Protocol - Convention on Climate Change - Greenhouse Gases (GHGs)
Aliphatic hydrocarbons	142-82-5	No
Xylene	1330-20-7	No
Ethyl benzene	100-41-4	No

Product Identifier: Rubber Buffer Stock Number: A586 Date of the latest revision of the safety data sheet: 04-12-2017 Supercedes:

Montreal Protocol on Substances that Deplete the Ozone Layer:

Chemical Name	CAS No	Montreal Protocol on Substances that Deplete the Ozone Layer
Aliphatic hydrocarbons	142-82-5	No
Xylene	1330-20-7	No
Ethyl benzene	100-41-4	No

Basel Convention on the Control of Transboundary Movements of Hazardous Wastes and their Disposal.:

Chemical Name	CAS No	Basel Convention on the Control of Transboundary Movements of Hazardous Wastes and their Disposal.
Aliphatic hydrocarbons	142-82-5	No
Xylene	1330-20-7	No
Ethyl benzene	100-41-4	No

16 Other information

Date of the latest revision of the safety data sheet:	04-12-2017
Revision Number:	2
Reason for revision:	Activated by Document Formulation Generation
Disclaimer:	IMPORTANT: WHILE THE DESCRIPTIONS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSINGOR APPLICATION/USE, WE RECOMMEND THAT YOU PERFORM AN ASSESSMENT TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED, DATA ORINFORMATION SET FORTH. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, OR DATA PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, THE DESCRIPTIONS, DATAAND INFORMATION FURNISHED HEREUNDER ARE GIVEN GRATIS. NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DATAAND INFORMATION GIVEN ARE ASSUMED. ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.