



# Safety Data Sheet

Issue Date: 07/09/2015

Revision Date: 07/09/2015

SDS Number: 15-RB-01  
Version: 1

## Section 1: Identification

### Product Identifier

Product Name: Rubber Buffer, Redi-Buffer

Catalog No: 1-722, 1-723, 1-724, 2-722, 2-723, 2-724, 4-722, 4-723, 4-724, BU16S, BU32, BUG

#### Other means of identification

SDS #: 15-RB-01

UN/ID No: UN1133

### Recommended use of Chemical & restriction on use

Recommended Use: Solvent

Restriction use: No further relevant information available

### Details of the supplier of the safety data sheet

Manufacturer/Supplier: ELGI Rubber Company, LLC  
600 N Magnolia Ave  
Luling, TX 78648  
Phone: (830) 875-5539  
Fax: (830) 875-5562

### Emergency Telephone Number

INFOTRAC Company Phone Number: +1 (352) 323-3500  
EMERGENCY Telephone (24hr): INFOTRAC +1 (352) 323-3500 (International)  
1-800-535-5053 (North America)

## Section 2: Hazards Identification


### Classification of the substance or mixture

OSHA/HCS status: This material is considered hazardous by the OSHA GHS Hazard Communication Standard (29 CFR 1910.1200).

Classifications:	Flam. Liq.	Category 2	H225 Highly flammable liquid and vapour.
	Asp. Tox.	Category 1	H304 May be fatal if swallowed and enters airways.
	Skin Irrit.	Category 2	H315 Causes skin irritation.
	STOT SE	Category 3	H336 May cause drowsiness or dizziness.
	Aquatic Acute	Category 1	H400 Very toxic to aquatic life.
Aquatic Chronic	Category 1	H410 Very toxic to aquatic life with long lasting effects.	

## GHS Label Elements

Pictograms:



Appearance: Clear liquid, Water-white

Physical State: Liquid

Odor: Petrolic

Signal Word: DANGER

Hazards Statements:

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary Statements - Prevention:

P210	Keep away from heat/sparks/open flames/hot surfaces - NO Smoking.
P233	Keep container tightly closed.
P240	Ground / bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating, and lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing mist / vapours.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves and eye / face protection.

Precautionary Statements - Response:

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P321	Specific treatment(see supplemental first aid instructions on this label).
P331	Do NOT induce vomiting.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362	Take off contaminated clothing and was before reuse.
P370 + P378	In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO2) for extinction.
P391	Collect spillage.

## Precautionary Statements - Storage:

P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

## Precautionary Statements - Disposal:

P501	Dispose of contents/container to an approved waste disposal plant.
------	--

**Hazards not otherwise classified (HNOC)**

Other Hazards:	Harmful to aquatic life with long lasting effects.
----------------	--

**Section 3: Composition/Information on Ingredients****Substances**

Components	CAS No	Weight-%
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	>=40-<50%
N-HEXANE	110-54-3	>=20-<30%
ACETONE	67-64-1	>=15-<20%
METHYL-3-PENTANE	96-14-0	>=1.5-<5%
METHYLCYCLOPENTANE	96-37-7	>=1.5-<5%
METHYL-2-PENTANE	107-83-5	>=1-<1.5%

**Section 4: First-Aid Measures****First Aid Measures**

Eye Contact:	Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.
Skin Contact:	Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.
Inhalation Contact:	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. Get immediate medical attention.
Ingestion Contact:	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If victim is conscious: Rinse mouth out with plenty of water. Let victim drink water as much as possible in small sips. Get immediate medical attention.

**Most Important Symptoms and Effects**

Symtoms:	Causes skin and eye irritation . Possible symptoms are irritation of the mucous membranes, dry cough and respiratory difficulty. Symptoms may include dizziness, headache, nausea and loss of coordination Suitable first-aid treatment should be immediately available. Seek medical advice before using product. May result in pulmonary oedema.
----------	--

## **Most Important Symptoms and Effects**

Notes to Physician: Hazards: Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion.

Treatment: No information available.

## **Section 5: Fire-Fighting Measures**

### **Suitable Extinguishing Media**

Suitable Extinguishing: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable Extinguishing: Do not use a solid water stream. Flash back possible over considerable distances.

### **Specific Hazards Arising from the Chemical**

\* Flammable, container may explode when heated. Flash back possible over considerable distances.

Hazardous Combustion Products: Carbon dioxide and Carbon monoxide.

Sensitivity to Static Discharge: No further relevant information available

### **Protective equipment and precautions for firefighters**

Advice for firefighters: Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). Water may be ineffective for extinguishment unless used under favorable conditions by experienced fire fighters. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

## **Section 6: Accidental Release Measures**

### **Personal precautions, protective equipment and emergency procedures**

Personal Precautions: Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Ensure adequate ventilation. Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Pay attention to the spreading of gases especially at ground level (heavier than air) and to direction of the wind.

For Emergency Responders: Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

**Precautions for Environments**

Environmental Precautions: Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

**Methods and materials for containment and cleaning up**

Methods for Containment: Contain spillage and ventilate area. Keep away from ignition sources (including static discharges). Evacuate area. Prevent evaporation by covering with foam.

Methods for Clean-up: Absorb excess liquid spillage on inorganic adsorbent material such as fine sand, brick dust etc. Place spent adsorbent in sealed packages and contact specialist waste disposal contractor.

**Section 7: Handling and Storage****Precautions for safe handling**

Advice on Safe Handling: Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.

**Conditions for safe storage, including any incompatibilities**

Storage Conditions: Store in a cool, dry, ventilated area, away from incompatible substances.

**Specific end use(s)**

Apart from the uses mentioned in section 1 no other specific uses are stipulated.

**Section 8: Exposure Controls/Personal Protection****Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
SOLVENT NAPHTHA (PETROLEUM) 64742-89-8	300 ppm (1,370 mg/m <sup>3</sup> ) TWA	500 ppm (2,000 mg/m <sup>3</sup> ) TWA	-
N-HEXANE 110-54-3	50 ppm TWA	500 ppm (1,800 mg/m <sup>3</sup> ) PEL	50 ppm (180 mg/m <sup>3</sup> ) REL
ACETONE 67-64-1	500 ppm TWA 750 ppm STEL	1,000 ppm (2,400 mg/m <sup>3</sup> ) PEL	250 ppm (590 mg/m <sup>3</sup> ) REL
METHYL-3-PENTANE 96-14-0	500 ppm TWA 1,000 ppm STEL	-	100 ppm (350 mg/m <sup>3</sup> ) REL 510 ppm (1,800 mg/m <sup>3</sup> ) Ceil
METHYL-2-PENTANE 107-83-5	500 ppm TWA 1,000 ppm STEL	-	100 ppm (350 mg/m <sup>3</sup> ) REL 510 ppm (1,800 mg/m <sup>3</sup> ) Ceil

Legend: ACGIH - American Conference of Governmental Hygienists  
OSHA - Occupational Safety and Health Administration  
NIOSH IDLH - The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

## **Appropriate engineering controls**

Engineering Controls: Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment. Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

## **Individual protection measures, such as personal protective equipment**

Eye/Face Protection: Wear splash resistant goggles or safety glasses that have been tested and approved under government standards.

Skin and Body Protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory Protection: Keep self contained breathing apparatus readily available for emergency use. If respiratory protection is needed, use only protection authorized in the U.S. Federal OSHA Standards(29CFR 1910.134), applicable U.S. State regulations, or Canadian CSA Standards Z94.4-93 and applicable standards of Canadian Provinces. Oxygen levels below pressure/demand SCBA or a full facepiece, supplied air respirator with auxiliary self-contained air supply is required under OSHA's Respiratory Protection Standards (1910.134-1998).

General Hygiene Considerations: Handle in accordance with good industrial hygiene and safety procedures. Refer to local regulations for restriction of waste disposal.

## **Section 9: Physical and Chemical Properties**

### **Information on basic physical and chemical properties**

Physical State: Liquid

Appearance: Clear liquid

Color: Clear, water-white

Odor: Petrolic

Odor Threshold: Not determined

pH:	Not determined
Melting Point/Freezing Point:	Not determined
Boiling Point/Boiling Range:	132.89 °F / 56.05 °C @ 1,013.25 hPa
Flash Point:	-8 °F / -22 °C Tag closed cup
Evaporation Rate:	Not determined
Flammability(solid, gas):	Not determined
Upper Flammability Limits:	12.8 %(V)
Lower Flammability Limits:	1.1% (V)
Vapor Pressure:	307.969 hPa @ 77 °F / 25 °C
Vapor Density:	Not determined
Specific Gravity:	0.698 g/cm <sup>3</sup> , 5.810 lb/gal @ 68 °F / 20 °C
Solubility in other Solvents:	Not determined
Partition Coefficient:	Not determined
Autoignition Temperature:	Not determined
Decomposition Temperature:	Not determined
Viscosity:	Not determined
Explosive Properties:	Not determined
Oxidizing Properties:	Not determined

### **Other safety information**

Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

## **Section 10: Stability and Reactivity**

### **Reactivity**

Not reactive under normal conditions.

### **Chemical Stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reaction**

Vapors may form explosive mixture with air

**Conditions to Avoid**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

**Incompatible Materials**

Strong oxidizing agents

**Hazardous Decomposition Products**

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

If involved in a fire the following toxic and/or corrosive fumes may be produced by thermal decomposition: Carbon dioxide and Carbon monoxide.

**Section 11: Toxicological Information****Information on likely routes of Exposure**

Eye Contact: Cause severe eye irritation  
Skin Contact: Cause skin irritation  
Inhalation: May be harmful if inhaled,  
Ingestion: May be harmful if swallowed

**Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	LD 50 Rat: > 8,000 mg/kg	LD 50 Rat: > 4,000 mg/kg	LC 50 Rat: 3400 ppm; 4 h
N-HEXANE	LD 50 Rat: 25 g/kg	LD 50 Rabbit: (>) 1.3 g/kg	LC 50 Rat: 48000 ppm; 4 h
ACETONE	LD 50 Rat: 5,800 mg/kg	LD 50 Rabbit: > 20,000 mg/kg	LC 50 Rat: > 16000 ppm; 4 h
METHYL-3-PENTANE	No data available	No data available	No data available
METHYLCYCLOPENTANE	LD 50 Rat: > 3,200 mg/kg	LD 50 Rabbit: > 86,700 mg/kg	LC 50 Rat: > 4044 ppm; 4 h
METHYL-2-PENTANE	No data available	No data available	LC 50 Rat: 3125 ppm; 4 h

symptoms: Please see section 4 of this SDS for symptom information.

Carcinogenicity: This product contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

Reproductive Toxicity: No data available

STOT-single exposure: May cause drowsiness or dizziness.

STOT-repeated exposure: May cause skin dryness or cracking.  
May result in skin and/or respiratory sensitivity.

Aspiration Hazard: May be fatal if swallowed and enters airways.



## Section 12: Ecological Information

### Ecotoxicity

Toxicity to fish: 96 h static test LC 50 Rainbow trout, donaldson trout (*Oncorhynchus mykiss*): 4,740.00 - 6,330.00 mg/l, 96 h static test LC 50 Bluegill (*Lepomis macrochirus*): 8,300.00 mg/l, 96 h flow-through test LC 50 Fathead minnow (*Pimephales promelas*): 8,733.00 - 9,482.00 mg/l, 96 h LC 50 Fish: 72.00 mg/l

Toxicity to daphnia and other aquatic invertebrates:

48 h EC 50 Water flea (*Daphnia magna*): 3.78 mg/l

### Persistence and degradability

Ratio BOD/ThBOD 3.5 %

### Bioaccumulative potential

Indication of bioaccumulation.

### Mobility in soil

no data available

### Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

### Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life with long lasting effects.

Do not empty into drains. Avoid release to the environment.

## Section 13: Disposal Considerations

### Waste Treatment Methods

Product: Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state, and local requirements.

Contaminated Packaging: Disposal should be in accordance with applicable regional, national and local laws and regulations.

## Section 14: Transport Information

### DOT

UN/ID No:	UN1133
Proper Shipping Name:	Rubber Adhesive
Hazard Class:	3
Packing Group:	II
Environmental Hazards:	No
Special Provisions:	Based on packaging size, product may be eligible for limited quantity exceptions or reclassified as ORM-D.

### IATA

UN/ID No:	UN1133
Proper Shipping Name:	Rubber Adhesive
Hazard Class:	3
Packing Group:	II
Environmental Hazards:	No
Special Provisions:	Based on packaging size, product may be eligible for limited quantity exceptions or reclassified as ORM-D.

### IMDG

UN/ID No:	UN1133
Proper Shipping Name:	Rubber Adhesive
Hazard Class:	3
Packing Group:	II
EMS:	F-E, S-D
Environmental Hazards:	Yes
Special Provisions:	Based on packaging size, product may be eligible for limited quantity exceptions or reclassified as ORM-D

### Special Precautions

Transport within user's premises:	Always transport in closed containers that are upright and secure. Ensure that personal transporting the product know what to do in the event of an accident or spillage.
Transport in bulk:	According to Annex II of MARPOL 73/78 and the IBC Code.

## Section 15: Regulatory Information

### U.S. Federal Regulations

SARA 311/312 Hazards:	Fire Hazard, Acute Health Hazard
SARA 302 Reportable Quantity:	This material does not contain any components with a SARA 302 RQ.
SARA 302 Threshold Planning Quantity:	SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SARA 304 Reportable Quantity:	This material does not contain any components with a section 304 EHS RQ.
SARA 313 Ingredients:	N-Hexane 28.23%
CERCLA Component Analysis:	US. EPA CERCLA Hazardous Substances (40 CFR 302.4), 17709lbs
TSCA Component Analysis:	Components of this product have been checked against the nonconfidential TSCA inventory by CAS Registry Number. Components not identified on this nonconfidential inventory are either exempt from listing (i.e. polymers, hydrates) or are listed on the confidential inventory as declared by the supplier. Component Analysis - Inventory
CAS # TSCA CAN EEC:	Heptane (n-) 142-82-5, Yes DSL EINECS

### Right-to-Know

Pennsylvania Right To Know Components:	Solvent Naphtha (Petroleum), Light Aliphatic 64742-89-8 N-Hexane 110-54-3 Acetone 67-64-1 Methyl-3-Pentane 96-14-0 Methylcyclopentane 96-37-7 Methyl-2-Pentane 107-83-5
New Jersey Right To Know Components:	Solvent Naphtha (Petroleum), Light Aliphatic 64742-89-8 N-Hexane 110-54-3 Acetone 67-64-1 Methyl-3-Pentane 96-14-0 Methylcyclopentane 96-37-7 Methyl-2-Pentane 107-83-5
California Prop. 65 Components:	This product does contain known to State of California to cause cancer, birth defects, or any other reproductive harm.

### Canadian Regulations

WHMIS Classification:	Class B-2: Flammable & Combustible Materials Class D-2A & D-2B: Material Causing other Toxic Effects
WHMIS IDL Component Analysis:	The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List.

## Section 16: Other Information

### NFPA Classification

Health Hazard: 2  
Fire Hazard: 3  
Reactivity Hazard: 0

### HMIS Classification

Health Hazard: 2  
Fire Hazard: 3  
Reactivity Hazard: 0

### Other Information

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

Revision Number: 1

Revision Date: 07/09/2015

SDS Prepared by: Victor Contreras (Approved by Rex Hidle)

## DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

The information in this document is believed to be correct as of the date issued. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM HAZARDS RELATED TO ITS USE. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assumes the risk of his use thereof.