

 Safety Data Sheet

 According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

 Revision Date: 10/30/2015
 Date of issue: 10/30/2015

Version: 1.0

SECTION 1: IDENTIFICATION

Product Identifier Product Form: Mixture Product Name: #105 Grease

Intended Use of the Product

Lubricating grease.

Name, Address, and Telephone of the Responsible Party

Company Ingersoll Rand 800-A Beaty Street, P.O. Box 1600 Davidson, NC 28036 T 1-800-483-4981 (Product Support)

Manufacturer

Fuchs Lubricants Co. Address: 17050 Lathrop Avenue Harvey, IL 60426 Telephone: 708-333-8900 Fax: 708-333-9180

Emergency Telephone Number

Emergency Number : 24-hour emergency Chemtrec numbers: Inside US: 1-800-424-9300 Outside US: 703-527-3887

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS-US classification Skin Irrit. 2 H315 Eye Irrit. 2A H319 Full text of H-phrases: see section 16

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)

	GHS07
Signal Word (GHS-US)	: Warning
Hazard Statements (GHS-US)	: H315 - Causes skin irritation.
	H319 - Causes serious eye irritation.
Precautionary Statements (GHS-US)	: P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
	P280 - Wear protective gloves, protective clothing, and eye protection.
	P302+P352 - If on skin: Wash with plenty of water.
	P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
	P321 - Specific treatment (see section 4 on this SDS).
	P332+P313 - If skin irritation occurs: Get medical advice/attention.
	P337+P313 - If eye irritation persists: Get medical advice/attention.
	P362+P364 - Take off contaminated clothing and wash it before reuse.

Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>Mixture</u>			
Name	Product Identifier	% (w/w)	GHS-US classification
Distillates, petroleum, hydrotreated heavy naphthenic	(CAS No) 64742-52-5	30 - 50	Not classified
Residual oils, petroleum, solvent-dewaxed	(CAS No) 64742-62-7	20 - 40	Not classified

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Distillates, petroleum, solvent-refined heavy paraffinic	(CAS No) 64741-88-4	10 - 20	Not classified
Calcium stearate	(CAS No) 1592-23-0	1 - 5	Comb. Dust
Sodium hydroxide	(CAS No) 1310-73-2	0.1 - 1	Met. Corr. 1, H290 Acute Tox. 4 (Dermal), H312 Skin Corr. 1A, H314 Eye Dam. 1, H318 Aquatic Acute 3, H402

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes serious eye irritation. Causes skin irritation.

Inhalation: Prolonged exposure may cause irritation.

Skin Contact: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Eye Contact: Contact causes severe irritation with redness and swelling of the conjunctiva.

Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, or dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection. **Hazardous Combustion Products**: Under fire conditions this material may produce hazardous carbon dioxide (CO₂), carbon monoxide (CO), various low molecular weight hydrocarbons, and smoke.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid breathing fumes. Avoid all contact with skin, eyes, or clothing.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams. **Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material, then place in suitable container. Contact competent authorities after a spill.

Reference to Other Sections

See Heading 8. Exposure controls and personal protection. See Section 13, Disposal Considerations.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Practice good housekeeping - spillage can be slippery on smooth surface.

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact with skin, eyes and clothing. Avoid breathing fumes.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong oxidizers.

Specific End Use(s)

Lubricating grease.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government

Sodium hydroxide (1310-73	-2)	
Mexico	OEL Ceiling (mg/m ³)	2 mg/m ³
USA ACGIH	ACGIH Ceiling (mg/m ³)	2 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	2 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	2 mg/m ³
USA IDLH	US IDLH (mg/m ³)	10 mg/m ³
Alberta	OEL Ceiling (mg/m ³)	2 mg/m ³
British Columbia	OEL Ceiling (mg/m ³)	2 mg/m ³
Manitoba	OEL Ceiling (mg/m ³)	2 mg/m ³
New Brunswick	OEL Ceiling (mg/m ³)	2 mg/m ³
Newfoundland & Labrador	OEL Ceiling (mg/m ³)	2 mg/m ³
Nova Scotia	OEL Ceiling (mg/m ³)	2 mg/m ³
Nunavut	OEL Ceiling (mg/m ³)	2 mg/m ³
Northwest Territories	OEL Ceiling (mg/m ³)	2 mg/m ³
Ontario	OEL Ceiling (mg/m ³)	2 mg/m ³
Prince Edward Island	OEL Ceiling (mg/m ³)	2 mg/m ³
Québec	PLAFOND (mg/m³)	2 mg/m ³
Saskatchewan	OEL Ceiling (mg/m ³)	2 mg/m ³
Yukon	OEL Ceiling (mg/m ³)	2 mg/m ³
Particulates not otherwise of	lassified (PNOC) (RR-00072-6)	
USA ACGIH	ACGIH TWA (mg/m³)	3 mg/m ³ Respirable fraction

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

		10 mg/m ³ Total Dust
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m ³ Respirable fraction
		15 mg/m ³ Total Dust
Alberta	OEL TWA (mg/m ³)	10 mg/m ³ (total)
		3 mg/m ³ (respirable)
British Columbia	OEL TWA (mg/m³)	10 mg/m ³ (total dust)
		3 mg/m ³ (respirable fraction)
Manitoba	OEL TWA (mg/m³)	10 mg/m ³ (inhalable particles, recommended)
		3 mg/m ³ (respirable particles, recommended)
New Brunswick	OEL TWA (mg/m³)	3 mg/m ³ (particulate matter containing no Asbestos and
		<1% Crystalline silica, respirable fraction)
		10 mg/m ³ (particulate matter containing no Asbestos and
		<1% Crystalline silica, inhalable fraction)
Newfoundland & Labrador	OEL TWA (mg/m³)	10 mg/m ³ (inhalable particles, recommended)
		3 mg/m ³ (respirable particles, recommended)
Nova Scotia	OEL TWA (mg/m³)	10 mg/m ³ (inhalable particles, recommended)
		3 mg/m ³ (respirable particles, recommended)
Nunavut	OEL TWA (mg/m³)	5 mg/m ³ (respirable mass)
		10 mg/m ³ (total mass)
Northwest Territories	OEL STEL (mg/m³)	20 mg/m ³ (insoluble or poorly soluble-inhalable fraction)
		6 mg/m ³ (insoluble or poorly soluble-respirable fraction)
Northwest Territories	OEL TWA (mg/m³)	10 mg/m ³ (insoluble or poorly soluble-inhalable fraction)
		3 mg/m ³ (insoluble or poorly soluble-respirable fraction)
Ontario	OEL TWA (mg/m³)	10 mg/m ³ (inhalable)
		3 mg/m ³ (respirable)
Prince Edward Island	OEL TWA (mg/m³)	10 mg/m ³ (inhalable particles, recommended)
		3 mg/m ³ (respirable particles, recommended)
Québec	VEMP (mg/m³)	10 mg/m ³ (including dust, inert or nuisance particulates-
		total dust)
Saskatchewan	OEL STEL (mg/m³)	20 mg/m ³ (insoluble or poorly soluble-inhalable fraction)
		6 mg/m ³ (insoluble or poorly soluble-respirable fraction)
Saskatchewan	OEL TWA (mg/m³)	10 mg/m ³ (insoluble or poorly soluble-inhalable fraction)
		3 mg/m ³ (insoluble or poorly soluble-respirable fraction)

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear protective gloves.

Eye Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. **Other Information:** When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties
Physical State : Solid

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

According To Federal Register / Vol. 77, No. 58 / Monday, March 2 Appearance		Black grease
Odor	:	5
	•	Mild petroleum
Odor Threshold	:	Not available
рН	:	Not available
Evaporation Rate	:	Not available
Melting Point	:	Not available
Freezing Point	:	Not available
Boiling Point	:	Not available
Flash Point	:	160 °C (320 °F)
Auto-ignition Temperature	:	Not available
Decomposition Temperature	:	Not available
Flammability (solid, gas)	:	Not available
Lower Flammable Limit	:	Not available
Upper Flammable Limit	:	Not available
Vapor Pressure	:	Not available
Relative Vapor Density at 20 °C	:	Not available
Specific Gravity	:	0.92
Solubility	:	Insoluble in water
Partition Coefficient: N-Octanol/Water	:	Not available
Viscosity	:	> 20.5 mm²/s @ 40 °C (104 °F)
Explosion Data – Sensitivity to Mechanical Impact	:	Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	:	Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

<u>Reactivity</u>: Hazardous reactions will not occur under normal conditions.

<u>Chemical Stability</u>: Stable under recommended handling and storage conditions (see section 7).

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

<u>Conditions to Avoid</u>: Direct sunlight, extremely high or low temperatures, and incompatible materials.

Incompatible Materials: Strong oxidizers.

Hazardous Decomposition Products: Under fire conditions this material may produce hazardous carbon dioxide (CO₂), carbon monoxide (CO), various low molecular weight hydrocarbons, and smoke.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes skin irritation.

Serious Eye Damage/Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Injuries After Eye Contact: Contact causes severe irritation with redness and swelling of the conjunctiva.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)			
LD50 Oral Rat	> 5000 mg/kg		
LD50 Dermal Rat	> 2000 mg/kg		
LC50 Inhalation Rat	> 5 mg/l/4h		
Residual oils, petroleum, solvent-dewaxed (64742-62-7)			
LD50 Oral Rat	> 5000 mg/kg		
LD50 Dermal Rabbit	> 2000 mg/kg		
LC50 Inhalation Rat	2.18 mg/l/4h		
Distillates, petroleum, solvent-refined heavy paraffinic (6474	Distillates, petroleum, solvent-refined heavy paraffinic (64741-88-4)		
LD50 Oral Rat	> 5000 mg/kg		
LD50 Dermal Rabbit	> 2000 mg/kg		
LC50 Inhalation Rat	2.18 mg/l/4h		
Calcium stearate (1592-23-0)			
LD50 Oral Rat	> 10 g/kg		
Sodium hydroxide (1310-73-2)			
LD50 Dermal Rabbit	1350 mg/kg		

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Not classified.

Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)		
LC50 Fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)	
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
Residual oils, petroleum, solvent-deway	xed (64742-62-7)	
LC50 Fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)	
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
Distillates, petroleum, solvent-refined h	neavy paraffinic (64741-88-4)	
LC50 Fish 1	5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)	
EC50 Daphnia 1	1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
Sodium hydroxide (1310-73-2)		
LC50 Fish 1	45.4 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])	
EC50 Daphnia 1	40 mg/l	
Persistence and Degradability		
#105 Grease		
Persistence and Degradability	Not established.	
Bioaccumulative Potential		
#105 Grease		
Bioaccumulative Potential	Not established.	
Mobility in Soil Not available		

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions.

Ecology – Waste Materials: Avoid release to the environment.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 14: TRANSPORT INFORMATION

In Accordance with DOT	Not regulated for transport.
In Accordance with IMDG	Not regulated for transport.
In Accordance with IATA	Not regulated for transport.

In Accordance with TDG Not regulated for transport.

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

#105 Grease

SARA Section 311/312 Hazard Classes

Immediate (acute) health hazard

Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Residual oils, petroleum, solvent-dewaxed (64742-62-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Distillates, petroleum, solvent-refined heavy paraffinic (64741-88-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Calcium stearate (1592-23-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Sodium hydroxide (1310-73-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SARA Section 311/312 Hazard Classes Immediate (acute) health hazard

US State Regulations

Sodium hydroxide (1310-73-2)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

U.S. - Pennsylvania - RTK (Right to Know) List

Canadian Regulations

#105 Grease

Class D Division 2 Subdivision B - Toxic material causing other toxic effects

T	
Ċ	

WHMIS Classification

Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)		
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria	
Residual oils, petroleum, so	lvent-dewaxed (64742-62-7)	
Listed on the Canadian DSL	(Domestic Substances List)	
WHMIS Classification Uncontrolled product according to WHMIS classification criteria		
Distillates, petroleum, solvent-refined heavy paraffinic (64741-88-4)		
Listed on the Canadian DSL	(Domestic Substances List)	
WHMIS Classification Uncontrolled product according to WHMIS classification criteria		
Calcium stearate (1592-23-0)		
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification Uncontrolled product according to WHMIS classification criteria		
Sodium hydroxide (1310-73-2)		
Listed on the Canadian DSL (Domestic Substances List)		

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Listed on the Canadian IDL (Ingredient Disclosure List)			
IDL Concentration 1 %			
WHMIS Classification	WHMIS Classification Class E - Corrosive Material		
Class D Division 2 Subdivision B - Toxic material causing other toxic effects			

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Re	evis	ion	Date	
	-		-	

: 10/30/2015

Other Information

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Comb. Dust	May form combustible dust concentrations in air
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Irrit. 2	Skin corrosion/irritation Category 2
H290	May be corrosive to metals
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H402	Harmful to aquatic life
	Causes serious eye irritation

Party Responsible for the Preparation of This Document

Ingersoll Rand 1-800-483-4981

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS