



MARVEL OIL CO., INC.  
625 WILLOWBROOK CTR PKWY  
WILLOWBROOK, IL 60527

## SAFETY DATA SHEET

### 1. Product and Company Identification

#### 1.1 Product Identifier

Product Name: Marvel Air Tool Oil  
Product Code (SKU): MM85R1 (50100), MM080R (50093) - See Section 15 for discontinued SKU's

#### 1.2 Relevant Identified Uses Of The Substance

Product Use: Engine Oil Additive – Fuel additive (EPA Registered)

#### 1.3 Details of the Supplier of the SDS

Company Name: Marvel Oil Company, Inc.  
Street Address: 625 Willowbrook Centre Parkway  
City, State, Zip Code: Willowbrook, Illinois 60527

#### 1.4 Emergency Telephone Numbers

Phone Number: 1(630)455-3700  
Fax Number: 1(630)455-3868  
Transportation: 1(800)424-9300 (CHEMTREC)  
Medical Assistance: Call your local Poison Control Center

### 2. Hazard Identification:

#### 2.1 Classification of the Substance or Mixture

Hazard Classification: Flammable liquid 3  
Skin irritation 2  
Reproductive Toxicity 2  
Aspiration toxicity 1

#### 2.2 Label Elements



Pictogram:

Signal Word: Danger

Hazard Statement: Flammable liquid and vapor. Causes skin irritation.  
Suspected of damaging fertility of the un-born child. May be fatal if swallowed and enters airways.

Precautionary Statement: Keep away from heat, sparks, open flames or hot surfaces. Do not smoke. Keep containers tightly closed. Ground all containers and receiving equipment. Use explosion proof electrical, ventilation, and lighting equipment. Use only non-sparking tools. Take precautionary measures against static

discharge. Wear protective gloves, clothing, eye glasses and face shield. Do not handle until all safety precautions have been read and understood. Wash hands thoroughly after handling. If exposed, get medical attention. If on skin or hair, remove immediately all contaminated clothing and launder before re-use. Wash skin with soap and water. If skin irritation occurs, get medical attention. If swallowed, immediately call a poison control center or doctor. Do NOT induce vomiting. Store in a well ventilated place. Dispose of contents and container in accordance with all local, state, national and international regulations.

### 2.3 Other Hazards

Description of additional HNOC: None

### 3. Information on Ingredients:

3.1 Substance not applicable

#### 3.2 Mixture

Component	CAS Number	Concentration (wt%)
Petroleum Distillates (Hydrotreated Heavy Naphthenic)	64742-52-5	60-100%
Petroleum Distillates (Stoddard Solvent)	8052-41-3	10-30%
Tricresyl Phosphate	1330-78-5	0.1-1.0%
Ortho Dichlorobenzene	95-50-1	0.1-1.0%
Para Dichlorobenzene	106-46-7	<0.1%

### 4. First Aid Measures:

#### 4.1 Description of First Aid Measures

Inhalation: Remove to fresh air and promote deep breathing. Get medical attention if effects persist or you feel un-well.

Skin: In case of skin contact, wash thoroughly with soap and water. Remove contaminated clothing and footwear. Launder clothing before re-use. Call a physician if irritation develops or persists.

Eyes: In case of eye contact, immediately flush eyes with plenty of water. Remove contact lenses if worn. If irritation persists, get medical attention

Ingestion: If swallowed, do not induce vomiting. Never give anything by mouth to an unconscious person. Immediately call a poison control center or physician.

#### 4.2 Most important symptoms and effects – acute and chronic

Inhalation: May cause respiratory tract irritation. Vapors may cause drowsiness or dizziness.

Skin: Cause skin irritation. Symptoms may include redness, edema, drying, defatting, and cracking of skin.

Eyes: May cause temporary eye irritation. Symptoms may include discomfort or pain, excess blinking and tearing, with redness and swelling.

Ingestion: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea, and vomiting.

#### 4.3 Indication of any immediate medical attention and special treatment

Symptoms may not appear immediately. Seek medical attention if effects develop or persist and you feel un-well.

### 5. Fire Fighting Measures:

#### 5.1 Extinguishing media

Carbon dioxide, dry chemical, and alcohol foam

#### 5.2 Special hazards arising from the substance or mixture

CO<sub>2</sub>, CO, and hydrocarbons

#### 5.3 Advice for Fire Fighters

Keep up wind of fire. Wear full firefighting turn out gear (full bunker gear) and respiratory protection (SCBA). Cool closed containers exposed to fire with water. See Section 8 for personal protection.

### 6. Accidental Release Measures:

#### 6.1 Personal precautions, protective equipment, and emergency procedures

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate all source of ignition.

#### 6.2 Methods and materials for containment and clean up

For containment: Contain and absorb spill with inert material. Place in suitable container for disposal. Do not flush to sewer or allow to enter waterways. See section 8 for PPE.

For clean up: Take up material and place in a suitable container. Vapors may be heavier than air and may travel along the ground to a distant source of ignition. Provide adequate ventilation.

### 7. Handling and Storage

#### 7.1 Precautions for safe handling

Keep away from source of ignition. Do not smoke. Take precaution to eliminate static discharge. Avoid contact with skin and eyes. Avoid breathing vapor or mist. Do not swallow. Do not eat or drink while handling. Wash hands with soap and water after handling. Use only non-sparking tools.

#### 7.2 Conditions for safe storage including incompatibilities

Keep out of reach of children. Store in a well ventilated place. Do not store above 49°C (120°F).

#### 7.3 Specific end uses

Shelf Life: Shelf life is considered to be 7 – 10 years when properly stored.

### 8. Exposure Control/Personal Protection:

#### 8.1 Control parameters

<u>Exposure Limits 8 hr TWA:</u>	<u>(OSHA PEL)</u>	<u>(ACGIH TWA)</u>
Petroleum Distillates (Hydrotreated Heavy Naphthenic)	not applicable	not applicable
Petroleum Distillates (Stoddard Solvent)	500 ppm	100 ppm
Tricresyl Phosphate	not applicable	not applicable
Ortho Dichlorobenzene	50 ppm	25 ppm
Para Dichlorobenzene	75 ppm	10 ppm

## 8.2 Exposure controls

Use adequate ventilation to keep exposure below recommended limits. Ensure that eye wash station and safety shower are close to work station.

Hand Protection Equipment: Wear chemical resistant gloves to prevent skin contact.

Eye Protection Equipment: Wear safety glasses or splash goggles to prevent eye contact.

Skin and Body Protection: Wear suitable protective clothing.

Respiration/Ventilation Protection Requirements: Provide good ventilation.

Ingestion Protection Requirements: Do not eat, drink or smoke while handling. Wash hands with soap and water after handling. Launder all clothing and foot wear before re-use.

## 9. Physical And Chemical Properties:

### 9.1 Information of basic chemical and physical properties

Physical Form: thin liquid

Color: clear red

Odor: typical oily

Odor Threshold: not available

pH: not applicable – oil based product

Melting Point/Freeze Point: -51°C (-60°F)

Initial Boiling Point: not available

Flash Point (Seta Closed Cup): 53°C (128°F)

Flammability Limits: Explosive Limits: Upper: not available Lower: not available

Evaporation Rate: not available

Flammability Solid/Gas: not applicable

Vapor Pressure: not available

Vapor Density: not available

Specific Gravity: 0.876

Solubility in Water: insoluble

Auto Ignition Temperature: not available

Partition coefficient (n/octanol/water): not available

Viscosity (Kinimatic @ 100°C): 2.0 – 3.0 cSt

### 9.2 Other information

% NVM by Weight: 75.0%

% VOC Content (California): 24.92%

## 10. Stability and Reactivity:

### 10.1 Reactivity

Does not react under normal conditions

### 10.2 Chemical stability

Stable

10.3 Possibility of hazardous reactions  
Does not react under normal conditions

10.4 Conditions to avoid  
Heat and incompatible materials

10.5 Incompatible materials  
Strong oxidizers such as bleach and peroxides

10.6 Hazardous decomposition products  
CO<sub>2</sub>, CO and hydrocarbons

## 11. Toxicological Information:

### 11.1 Information on Toxicological effects

#### Marvel Mystery Oil

LD50 – Oral Rat >2000 mg/Kg  
LD50 – Dermal Rabbit >2000 mg/Kg  
LC50 – Inhalation Rat >20 mg/L (4 hr)

#### Petroleum Distillates Hydrotreated Heavy Naphthenic (64742-52-5)

LD50 – Oral Rat >5000 mg/Kg  
LD50 – Dermal Rabbit >5000 mg/Kg  
LC50 – Inhalation Rat >5 mg/L (4 hr)

#### Tricresyl Phosphate (1330-78-5)

LD50 – Oral Rat 3000 mg/Kg

#### o-Dichlorobenzene (95-50-1)

LD50 – Oral Rat 500 mg/Kg  
LD50 – Dermal Rabbit >10000 mg/Kg  
LC50 – Inhalation Rat 8.15 mg/L (4 hr)

#### p-Dichlorobenzene (106-46-7)

LD50 – Oral Rat >2000 mg/Kg  
LD50 – Dermal Rabbit >2000 mg/Kg

Skin corrosion/irritation	Causes skin irritation
Serious eye damage/irritation	Based on available data, classification data are not met
Respiratory or skin sensitization	Based on available data, classification data are not met
Germ cell mutagenicity	Based on available data, classification data are not met
Carcinogenicity	Based on available data, classification data are not met

o-Dichlorobenzene (95-50-1)	IARC Group 3 – Not Classified
p-dichlorobenzene (106-46-7)	IARC Group 2B – Possible carcinogen to humans. NTP 1-Evidence of Carcinogenicity 3, Reasonably anticipated to be a human Carcinogen

Reproductive toxicity	Suspected of damaging fertility of un-born child
Specific target organs – single exposure	Based on available data, classification data are not met
Specific target organs – repeated exposure	Based on available data, classification data are not met

Aspiration hazard	May be fatal if swallowed and enters air ways.
Symptoms/injuries after inhalation	May cause respiratory tract irritation. Vapors may cause drowsiness and dizziness.
Symptoms/injuries after skin contact	Cause skin irritation. Symptoms may include redness, edema, drying, defatting, and cracking of skin.
Symptoms/injuries after eye contact	May cause temporary eye irritation. Symptoms may include discomfort or pain, excess blinking and tearing, with redness and swelling.
Symptoms/injuries after ingestion	May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea, and vomiting.

12. Ecological Information:

12.1 Toxicity

Not recommended for release into aquatic systems without treatment

12.2 Persistence and degradability

Not established

12.3 Bioaccumulative potential

Not established

12.4 Mobility in soil

Not established

12.5 Other adverse effects

None known

13. Disposal Considerations:

13.1 Waste treatment methods

RCRA Hazardous Waste:  
Waste Disposal Method:

Regulated as a hazardous waste (D-001 Ignitable).  
Dispose of in accordance with local, state and federal regulations

Waste Disposal Vessel:

Metal drums are recommended.

14. Transportation Information:

14.1 UN number

1268

14.2 UN Proper shipping name

Petroleum Distillate n.o.s.

14.3 Transport Hazard class

3

14.4 Packaging group

III

14.5 Marine Pollutant

No

14.6 Transportation in Bulk

Not applicable



This information is, to the best of Turtle Wax, Inc.'s knowledge and belief, accurate and reliable. However, no representation, warranty, or guarantee is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy oneself as to the suitability and completeness of such information for their own particular use.